

# Summary

- Color information can improve face perception
- Several cortical regions contain single neurons whose responses are influenced by color and shape simultaneously
- Cortical regions supporting color and face perception abilities are close
- ADC found literature supporting behavioral improvements in two domains: face detection and gender recognition
- Color may aid emotion recognition, but ADC only found computer vision literature supporting this

The references listed below are ones that support a role for color information in aiding face perception. The importance of the role depends strongly on the perceptual task in question, however. There is a long literature showing that ventral occipitotemporal cortical regions from V1 onwards contain single neurons that respond to specific combinations of shape and color features; only two references are included here. In as much as there exists a “color region” of cortex, it is located just posterior and medial to “face regions.” Color aids face detection, especially in naturalistic backgrounds, when it is done by both human observers and computer vision algorithms. Color appears to aid gender discrimination, although the specific color/gender associations seem up in the air. Not much research has been done on the role of color in recognizing facial expressions of emotion, but there is at least one computer vision article that found a use for color in that domain.

## FIRST OF ALL

Refer to this very comprehensive list of computer vision articles:

<http://www.visionbib.com/bibliography/people902.html#Finding%20Faces%20by%20Color%20Features>

For a list of computer vision face image data sets, navigate here and skip to *Dataset, Faces*. Note that this is not a complete list.

<http://datasets.visionbib.com/index.html>

See also VNLab's list of face image data sets available online:

[Face data sets](#)

## Close relationship between cortical regions for color and face perception

- Clark, V. P., Parasuraman, R., Keil, K., Kulansky, R., Fannon, S., Maisog, J. M., ... Haxby, J. V. (1997). Selective attention to face identity and color studied with f MRI. *Human Brain Mapping*, 5(4),

293–297. doi:10.1002/(SICI)1097-0193(1997)5:4<293::AID-HBM15>3.0.CO;2-F

- Tanaka, K., Saito, H., Fukada, Y., & Moriya, M. (1991). Coding visual images of objects in the inferotemporal cortex of the macaque monkey. *Journal of Neurophysiology*, 66(1), 170–189.

## Color aids face detection

### Behavioral

- Yip, Andrew W., and Pawan Sinha. "Contribution of Color to Face Recognition." *Perception* 31, no. 8 (2002): 995–1003. doi:10.1068/p3376.

NOTE: at least one article hints that if individuals can be distinguished based solely on color information, then ordinary, holistic face recognition processes might not be used:

- McKone, Elinor, and Galit Yovel. "Why Does Picture-plane Inversion Sometimes Dissociate Perception of Features and Spacing in Faces, and Sometimes Not? Toward a New Theory of Holistic Processing." *Psychonomic Bulletin & Review* 16, no. 5 (October 2009): 778–97. doi:10.3758/PBR.16.5.778.

### Computational

- Maglogiannis, Ilias, Demosthenes Vouyioukas, and Chris Aggelopoulos. "Face Detection and Recognition of Natural Human Emotion Using Markov Random Fields." *Personal and Ubiquitous Computing* 13, no. 1 (January 1, 2009): 95–101. doi:10.1007/s00779-007-0165-0.

## Color aids gender recognition

### Behavioral

- Hill, H., Bruce, V., & Akamatsu, S. (1995). Perceiving the sex and race of faces: the role of shape and colour. *Proceedings. Biological Sciences / The Royal Society*, 261(1362), 367–373. doi:10.1098/rspb.1995.0161
- Tarr, M. J., Kersten, D., Cheng, Y., & Rossion, B. (2001). It's Pat! Sexing faces using only red and green. *Journal of Vision*, 1(3), 337–337. doi:10.1167/1.3.337
- "The Segmental Structure of Faces and Its Use in Gender Recognition" Accessed August 5, 2014. <http://repository.cmu.edu/cgi/viewcontent.cgi?article=1392&context=psychology>.

# Color aids emotion recognition

## Computational

- Maglogiannis, Ilias, Demosthenes Vouyioukas, and Chris Aggelopoulos. "Face Detection and Recognition of Natural Human Emotion Using Markov Random Fields." *Personal and Ubiquitous Computing* 13, no. 1 (January 1, 2009): 95-101. doi:10.1007/s00779-007-0165-0.

## Detailed information for the references

Sorted by author and date.

```
<html> <head><meta http-equiv="Content-Type" content="text/html; charset=utf-8" /> <title>Zotero Report</title> <link rel="stylesheet" type="text/css" href="zotero:report/detail.css"/> <link rel="stylesheet" type="text/css" media="screen,projection" href="zotero:report/detail_screen.css"/> <link rel="stylesheet" type="text/css" media="print" href="zotero:report/detail_print.css"/> </head> <body> <ul class="report combineChildItems"> <li id="i22046" class="item journalArticle"> <h2>Color Face Recognition for Degraded Face Images</h2> <table> <tr> <th>Type</th> <td>Journal Article</td> </tr> <tr> <th class="author">Author</th> <td>Jae-Young Choi</td> </tr> <tr> <th class="author">Author</th> <td>Yong-Man Ro</td> </tr> <tr> <th class="author">Author</th> <td>K.N. Plataniotis</td> </tr> <tr> <th>Volume</th> <td>39</td> </tr> <tr> <th>Issue</th> <td>5</td> </tr> <tr> <th>Pages</th> <td>1217-1230</td> </tr> <tr> <th>Publication</th> <td>IEEE Transactions on Systems, Man, and Cybernetics, Part B: Cybernetics</td> </tr> <tr> <th>ISSN</th> <td>1083-4419</td> </tr> <tr> <th>Date</th> <td>October 2009</td> </tr> <tr> <th>DOI</th> <td>10.1109/TSMCB.2009.2014245</td> </tr> <tr> <th>Library Catalog</th> <td>IEEE Xplore</td> </tr> <tr> <th>Abstract</th> <td>In many current face-recognition (FR) applications, such as video surveillance security and content annotation in a Web environment, low-resolution faces are commonly encountered and negatively impact on reliable recognition performance. In particular, the recognition accuracy of current intensity-based FR systems can significantly drop off if the resolution of facial images is smaller than a certain level (e.g., less than 20 times 20 pixels). To cope with low-resolution faces, we demonstrate that facial color cue can significantly improve recognition performance compared with intensity-based features. The contribution of this paper is twofold. First, a new metric called "variation ratio gain" (VRG) is proposed to prove theoretically the significance of color effect on low-resolution faces within well-known subspace FR frameworks; VRG quantitatively characterizes how color features affect the recognition performance with respect to changes in face resolution. Second, we conduct extensive performance evaluation studies to show the effectiveness of color on low-resolution faces. In particular, more than 3000 color facial images of 341 subjects, which are collected from three standard face databases, are used to perform the comparative studies of color effect on face resolutions to be possibly confronted in real-world FR systems. The effectiveness of color on low-resolution faces has successfully been tested on three representative subspace FR methods, including the eigenfaces, the fisherfaces, and the Bayesian. Experimental results show that color features decrease the recognition error rate by at least an order of

```

magnitude over intensity-driven features when low-resolution faces (25 times 25 pixels or less) are applied to three FR methods.

Date Added	Tuesday, August 05, 2014 12:39:03 PM
Modified	Tuesday, August 05, 2014 12:39:03 PM

**Tags:** Algorithms Artificial Intelligence Bayesian Color color face recognition Color face recognition (FR) Colorimetry degraded face images eigenfaces Face face databases face recognition face resolution fisherfaces Humans Identification image colour analysis Image Interpretation, Computer-Assisted Pattern Recognition, Automated Subtraction Technique variation ratio gain variation ratio gain (VRG) verification (VER) video surveillance web-based FR

**Attachments:** IEEE Xplore Abstract Record

**Selective attention to face identity and color studied with fMRI**

Type	Journal Article
Author	Vincent P. Clark
Author	Raja Parasuraman
Author	Katrina Keil
Author	Rachel Kulansky
Author	Sean Fannon
Author	Jose Ma. Maisog
Author	Leslie G. Ungerleider
Author	James V. Haxby

**URL:** [http://onlinelibrary.wiley.com/doi/10.1002/\(SICI\)1097-0193\(1997\)5:4<293::AID-HBM15>3.0.CO;2-F/abstract](http://onlinelibrary.wiley.com/doi/10.1002/(SICI)1097-0193(1997)5:4<293::AID-HBM15>3.0.CO;2-F/abstract)

Rights	Published 1997 Wiley-Liss, Inc.
Volume	5
Issue	4
Pages	293-297
Publication	Human Brain Mapping
ISSN	1097-0193
Date	January 1, 1997
Journal Abbr	Hum. Brain Mapp.
DOI	10.1002/(SICI)1097-0193(1997)5:4<293::AID-HBM15>3.0.CO;2-F
Accessed	Tuesday, August 05, 2014 12:38:08 PM
Library Catalog	Wiley Online Library
Language	en
Abstract	Cortical areas associated with selective attention to the color and identity of faces were located using functional magnetic resonance imaging (fMRI). Six subjects performed tasks which required selective attention to face identity or color similarity using the same color-washed face stimuli. Performance of the color attention task but not the face attention task was associated with a region of activity in the collateral sulcus and nearby regions of the lingual and fusiform gyri. Performance of both tasks was associated with a region of activity in ventral occipitotemporal cortex that was lateral to the color responsive area and had a greater spatial extent. These fMRI results converge with results obtained from PET and ERP studies to demonstrate similar anatomical locations of functional areas for face and color processing across studies. Hum. Brain Mapping 5:293-297, 1997. Published 1997 Wiley-Liss, Inc. This article was prepared by a group consisting of both United States government employees and non-United States government employees, and as such is subject to 17 U.S.C. Sec. 105.

Date Added	Tuesday, August 05, 2014 12:38:08 PM
Modified	Tuesday, August 05, 2014 12:38:08 PM

**Tags:** Brain Mapping Color Perception

[extrastriate cortex](#) [face recognition](#) [Magnetic Resonance Imaging](#) [selective attention](#) [Visual Cortex](#) [Visual Pathways](#)

### Attachments

- Snapshot

- ## Combining color and shape information for illumination-viewpoint invariant object recognition

Type	Journal Article
Author	A Diplaros
Author	T. Gevers
Author	I Patras
Volume	15
Issue	1
Pages	1-11
Publication	IEEE Transactions on Image Processing
ISSN	1057-7149
Date	January 2006
DOI	10.1109/TIP.2005.860320
Library Catalog	IEEE Xplore
Abstract	In this paper, we propose a new scheme that merges color- and shape-invariant information for object recognition. To obtain robustness against photometric changes, color-invariant derivatives are computed first. Color invariance is an important aspect of any object recognition scheme, as color changes considerably with the variation in illumination, object pose, and camera viewpoint. These color invariant derivatives are then used to obtain similarity invariant shape descriptors. Shape invariance is equally important as, under a change in camera viewpoint and object pose, the shape of a rigid object undergoes a perspective projection on the image plane. Then, the color and shape invariants are combined in a multidimensional color-shape context which is subsequently used as an index. As the indexing scheme makes use of a color-shape invariant context, it provides a high-discriminative information cue robust against varying imaging conditions. The matching function of the color-shape context allows for fast recognition, even in the presence of object occlusion and cluttering. From the experimental results, it is shown that the method recognizes rigid objects with high accuracy in 3-D complex scenes and is robust against changing illumination, camera viewpoint, object pose, and noise.
Date Added	Tuesday, August 05, 2014 12:39:59 PM
Modified	Tuesday, August 05, 2014 12:39:59 PM

### Tags:

- Algorithms
- Artificial Intelligence
- camera viewpoint
- cameras
- cluttering
- Color
- Colorimetry
- color-invariant derivatives
- Color-shape context
- composite information
- geometric invariants
- illumination-viewpoint invariant object recognition
- image colour analysis
- Image Enhancement
- Image Interpretation, Computer-Assisted
- image matching
- Image recognition
- image retrieval
- Imaging, Three-Dimensional
- indexing scheme
- Information Storage and Retrieval
- Layout
- Lighting
- matching function
- multidimensional color-shape context
- Multidimensional systems
- object occlusion
- object pose
- object recognition
- Pattern Recognition, Automated
- photometric changes
- photometric invariants
- Photometry
- Robustness
- Shape
- similarity invariant shape descriptors
- Subtraction Technique

### Attachments

- IEEE Xplore Abstract Record- ## Perceiving the sex and race of faces: the role of shape and colour

Type	Journal Article
Author	H. Hill
Author	V. Bruce
Author	S. Akamatsu
Volume	261
Issue	1362
Pages	367-373
Publication	Proceedings. Biological Sciences / The Royal Society
ISSN	0962-8452
Date	Sep 22, 1995
Extra	

PMID: 8587879

Journal Abbr	Proc. Biol. Sci.
DOI	10.1098/rspb.1995.0161
Library Catalog	NCBI PubMed
Language	eng
Abstract	Theories of object recognition have emphasized the information conveyed by shape information, whereas theories of face recognition have emphasized properties of superficial features. In the experiments reported here we used novel technology to investigate the relative contributions of shape and superficial colour information to simple categorization decisions about the sex and 'race' of faces. The results show that both shape and colour provide useful information for these decisions; shape information was particularly useful for race decisions while colour dominated sex decisions. When both sources of information were combined, the dominant source depended on viewpoint, with angled views emphasizing the contribution of shape and the full-face view colour. The results are discussed within the context of theories of face recognition and their implications for telecommunication applications are considered.
Short Title	Perceiving the sex and race of faces
Date Added	Tuesday, August 05, 2014 12:36:25 PM
Modified	Tuesday, August 05, 2014 12:36:25 PM

### Tags:

- Adult
- Analysis of Variance
- Asian Continental Ancestry Group
- Continental Population Groups
- European Continental Ancestry Group
- Face
- Female
- Form Perception
- Humans
- Japan
- Male
- Sex Characteristics
- Skin Pigmentation

### Attachments

- PubMed entry
- Face detection and recognition of natural human emotion using Markov random fields

Type	Journal Article
Author	Ilias Maglogiannis
Author	Demosthenes Vouyioukas
Author	Chris Aggelopoulos
URL	<a href="http://link.springer.com/article/10.1007/s00779-007-0165-0">http://link.springer.com/article/10.1007/s00779-007-0165-0</a>
Volume	13
Issue	1
Pages	95-101
Publication	Personal and Ubiquitous Computing
ISSN	1617-4909, 1617-4917
Date	2009/01/01
Journal Abbr	Pers Ubiquit Comput
DOI	10.1007/s00779-007-0165-0
Accessed	Tuesday, August 05, 2014 12:40:15 PM
Library Catalog	link.springer.com
Language	en
Abstract	This paper presents an integrated system for emotion detection. In this research effort, we have taken into account the fact that emotions are most widely represented with eye and mouth expressions. The proposed system uses color images and it is consisted of three modules. The first module implements skin detection, using Markov random fields models for image segmentation and skin detection. A set of several colored images with human faces have been considered as the training set. A second module is responsible for eye and mouth detection and extraction. The specific module uses the HLV color space of the specified eye and mouth region. The third module detects the emotions pictured in the eyes and mouth, using edge detection and measuring the gradient of eyes' and mouth's region figure. The paper provides results from the system application, along with proposals for further research.
Date Added	Tuesday, August 05, 2014 12:40:15 PM
Modified	Tuesday, August 05, 2014 12:40:15 PM

### Tags:

- emotion recognition
- Face detection
- ICM
- image

segmentation

- Markov random field
- User Interfaces and Human Computer Interaction

### Attachments

- Snapshot
- Why does picture-plane inversion sometimes dissociate perception of features and spacing in faces, and sometimes not? Toward a new theory of holistic processing

Type	Journal Article
Author	Elinor McKone
Author	Galit Yovel
Volume	16
Issue	5
Pages	778-797
Publication	Psychonomic Bulletin & Review
ISSN	1531-5320
Date	Oct 2009
Extra	PMID: 19815781
Journal Abbr	Psychon Bull Rev
DOI	10.3758/PBR.16.5.778
Library Catalog	NCBI PubMed
Language	eng
Abstract	Classically, it has been presumed that picture-plane inversion primarily reduces sensitivity to spacing/configural information in faces (distance between location of the major features) and has little effect on sensitivity to local feature information (e.g., eye shape or color). Here, we review 22 published studies relevant to this claim. Data show that the feature inversion effect varied substantially across studies as a function of the following factors: whether the feature change was shape only or included color/brightness, the number of faces in the stimulus set, and whether the feature was in facial context. For shape-only changes in facial context, feature inversion effects were as large as typical spacing inversion effects. Small feature inversion effects occurred only when a task could be efficiently solved by visual-processing areas outside whole-face coding. The results argue that holistic/configural processing for upright faces integrates exact feature shape and spacing between blobs. We describe two plausible approaches to this process.
Short Title	Why does picture-plane inversion sometimes dissociate perception of features and spacing in faces, and sometimes not?
Date Added	Tuesday, August 05, 2014 12:38:38 PM
Modified	Tuesday, August 05, 2014 12:38:38 PM

### Tags:

- Face
- Form Perception
- Humans
- Individuality
- Models, Psychological
- Space Perception
- Visual Perception

### Attachments

- PubMed entry
- Coding visual images of objects in the inferotemporal cortex of the macaque monkey

Type	Journal Article
Author	K. Tanaka
Author	H. Saito
Author	Y. Fukada
Author	M. Moriya
Volume	66
Issue	1
Pages	170-189
Publication	Journal of Neurophysiology
ISSN	0022-3077
Date	Jul 1991
Extra	PMID: 1919665
Journal Abbr	J. Neurophysiol.
Library Catalog	NCBI PubMed
Language	eng
Abstract	1. The inferotemporal cortex (IT) has been thought to play an essential and specific role in visual object discrimination and recognition, because a lesion of IT in the monkey results in a specific deficit in learning tasks that require these visual functions. To understand the cellular basis of the object discrimination and recognition processes in IT, we determined the optimal stimulus of individual IT cells in anesthetized, immobilized monkeys. 2. In the posterior one-third or one-fourth of IT, most cells could be activated maximally by bars or disks just by adjusting the size, orientation, or color of the stimulus. 3. In the remaining anterior two-thirds or three-quarters of IT, most cells required more complex features

for their maximal activation. 4. The critical feature for the activation of individual anterior IT cells varied from cell to cell: a complex shape in some cells and a combination of texture or color with contour-shape in other cells. 5. Cells that showed different types of complexity for the critical feature were intermingled throughout anterior IT, whereas cells recorded in single penetrations showed critical features that were related in some respects. 6. Generally speaking, the critical features of anterior IT cells were moderately complex and can be thought of as partial features common to images of several different natural objects. The selectivity to the optimal stimulus was rather sharp, although not absolute. We thus propose that, in anterior IT, images of objects are coded by combinations of active cells, each of which represents the presence of a particular partial feature in the image.

Date Added	Tuesday, August 05, 2014 12:38:29 PM
Modified	Tuesday, August 05, 2014 12:38:29 PM

### Tags:

- Animals
- Brain Mapping
- Color
- Discrimination (Psychology)
- Macaca
- Neurons
- Photic Stimulation
- Temporal Lobe
- Visual Perception

### Attachments

- PubMed entry
- Pat! Sexing faces using only red and green

Type	Journal Article
Author	M. J. Tarr
Author	D. Kersten
Author	Y. Cheng
Author	B. Rossion
URL	<a href="http://www.journalofvision.org/content/1/3/337">http://www.journalofvision.org/content/1/3/337</a>

Volume	1
Issue	3
Pages	337-337
Publication	Journal of Vision
ISSN	, 1534-7362
Date	12/12/2001
Journal Abbr	J Vis
DOI	10.1167/1.3.337
Accessed	Tuesday, August 05, 2014 12:36:04 PM
Library Catalog	<a href="http://www.journalofvision.org">www.journalofvision.org</a>
Language	en
Abstract	The reflectance properties of facial hair and skin across sexes produce different degrees of red and green in male (more red) and female (more green) faces. Consequently, measuring the overall ratio of red/green energy in a face is sufficient for accurate sex classification. The optimal red/green threshold for discriminating 200 Caucasian faces by sex yielded an accuracy rate of 75% correct with a $d'$ of 2.0. Faces had no makeup and were edited to remove all hair around the head. A second set of Caucasian faces produced similar results. Preliminary analyses suggest that the red/green ratio is also sufficient for sex classification of Asian and African faces. In contrast, pre-pubescent Caucasian faces were classified at chance. Thus, the red/green difference between males and females may be attributed to post-puberty sexual dimorphism in the spectral properties of human faces. We compared these computational findings with the human ability to discriminate male faces from female faces. To prevent observers from relying on shape information useful for sex classification, the 200 Caucasian faces were dramatically blurred using a Gaussian filter. Faces were presented for 100ms and observers simply judged whether each face was male or female. For female faces there was a -0.66 correlation between red/green ratio and accuracy in sex classification; for males the correlation was +0.42. Reinforcing the relationship between our model and human performance, observers were at chance in their ability to discriminate pre-pubescent faces. Our results may provide a mechanism for rapid sex classification through the differential response of early color opponent processes to male and female faces. In sum, red/green energy appears to be a reliable cue for fast and accurate discrimination of faces by sex.
Date Added	

Tuesday, August 05, 2014 12:36:04 PM

Modified	Tuesday, August 05, 2014 12:36:04 PM
----------	--------------------------------------

### Attachments

- Snapshot
- item conferencePaper">

## The importance of the color information in face recognition

Type	Conference Paper
Author	L. Torres
Author	J. Y. Reutter
Author	L. Lorente
Volume	3
Pages	627-631 vol.3
Date	1999
DOI	10.1109/ICIP.1999.817191
Library Catalog	IEEE Xplore
Conference Name	1999 International Conference on Image Processing, 1999. ICIP 99. Proceedings
Abstract	A common feature found in practically all technical approaches proposed for face recognition is the use of only the luminance information associated to the face image. One may wonder if this is due to the low importance of the color information in face recognition or due to other less technical reasons such as the no availability of color image database. Motivated by this reasoning, we have performed a variety of tests using a global eigen approach developed previously, which has been modified to cope with the color information. Our results show that the use of the color information embedded in a eigen approach, improve the recognition rate when compared to the same scheme which uses only the luminance information
Proceedings Title	1999 International Conference on Image Processing, 1999. ICIP 99. Proceedings
Date Added	Tuesday, August 05, 2014 12:38:52 PM
Modified	Tuesday, August 05, 2014 12:38:52 PM

### Tags:

  - Availability
  - Color
  - color image database
  - color information
  - Covariance matrix
  - face image
  - face recognition
  - global eigen approach
  - image colour analysis
  - Image databases
  - Image recognition
  - luminance information
  - Performance evaluation
  - principal component analysis
  - reasoning
  - Testing
  - Vectors
  - visual databases

### Attachments

  - IEEE Xplore Abstract Record
  - item journalArticle">

## Contribution of color to face recognition

Type	Journal Article
Author	Andrew W. Yip
Author	Pawan Sinha
Rights	© 2012 APA, all rights reserved
Volume	31
Issue	8
Pages	995-1003
Publication	Perception
ISSN	1468-4233(Electronic);0301-0066(Print)
Date	2002
DOI	10.1068/p3376
Library Catalog	APA PsycNET
Abstract	One of the key challenges in face perception lies in determining how different facial attributes contribute to judgments of identity. This study focuses on the role of color cues. Although color appears to be a salient attribute of faces, past research has suggested that it confers little recognition advantage for identifying people. Using 37 subjects (aged 18-40 yrs) with normal or corrected-to-normal vision, the authors report experimental results suggesting that color cues do play a role in face recognition and their contribution becomes evident when shape cues are degraded. Under such conditions, recognition performance with color images is significantly better than that with gray-scale images. The results also indicate that the contribution of color may lie not so much in providing diagnostic cues to identity as in aiding low-level image-analysis processes such as segmentation.
Date Added	Tuesday, August 05, 2014 12:37:36 PM
Modified	Tuesday, August 05, 2014 12:37:36 PM

### Tags:

    - \*Color

</li>\*Cues</li> </li>\*Face Perception</li> </li>visual discrimination</li> </ul> <h3 class="attachments">Attachments</h3> <ul class="attachments"> <li id="i22037">APA PsycNET Snapshot</li> </ul> </li> <li id="i22035" class="item attachment"> <h2>The segmental structure of faces and its use in gender recognition - viewcontent.cgi</h2> <table> <tr> <th>Type</th> <td>Attachment</td> </tr> <tr> <th>URL</th> <td><a href="http://repository.cmu.edu/cgi/viewcontent.cgi?article=1392&context=psychology">http://repository.cmu.edu/cgi/viewcontent.cgi?article=1392&context=psychology</a></td> </tr> <tr> <th>Accessed</th> <td>Tuesday, August 05, 2014 12:37:04 PM</td> </tr> <tr> <th>Date Added</th> <td>Tuesday, August 05, 2014 12:37:04 PM</td> </tr> <tr> <th>Modified</th> <td>Tuesday, August 05, 2014 12:37:08 PM</td> </tr> </table></li> </ul> </body> </html>

From: <https://www.wiki.anthonycate.org/> - **Visual Cognitive Neuroscience**

Permanent link: [https://www.wiki.anthonycate.org/doku.php?id=resources:pdf\\_document\\_resources:topic\\_face\\_color](https://www.wiki.anthonycate.org/doku.php?id=resources:pdf_document_resources:topic_face_color)

Last update: **2023/10/14 21:29**

